

WEEK | ISSUED

BoF 5/06 B3F

XP-002193968

9326 / 18 AUG 93

Published June 30, 1992


P.D. 30-06-1992	1
P. 1	

★ KURI/ P64 93-212108/26 ★ SU 1743887-A1  
 Prodn. of foam for building slurries - involves mixing foaming  
 solution and air in sleeve with vortex-generating cavities  
 KURILOV V V 89.12.29 89SU-4783935  
 (92.06.30) B28C 5/38

Compressed air and foaming solution are fed into a vortex-generating sleeve (4) to create a high quality foam. The foam is discharged into a mixer (3). A compressed air feed pipe (1) and a foaming solution feed pipe (2) are set symmetrically about the axis of the mixing chamber.

The latter incorporates the sleeve with a series of open drop-shaped cavities which create turbulent flow conditions and intense mixing of the air and the solution. The vol. of the cavities increases or decreases along the length of the sleeve. The outlet end of the mixing chamber incorporates a grid (5).

ADVANTAGE - Improved quality of foam. (3pp Dwg.No.1/2)  
 N93-163065



© 1993 DERWENT PUBLICATIONS LTD.

Derwent House, 14 Great Queen Street, London WC2B 5DF England, UK

US Office: Derwent Inc., 1313 Dolley Madison Blvd., Suite 401, McLean VA 22101, USA

Unauthorised copying of this abstract not permitted



DERWENT

Scientific and Patent Information